Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1   **Claim 1 (previously presented):**   Handle (11) for a
2   hand held engine powered tool comprising at least a lever
3   or button for controlling the power of the tool, said
4   handle (11) is made of at least two handle sections (15,
5   16), said lever or button is secured in only one of the
6   handle sections (16) so that the function of the lever or
7   button is independent of the handle sections (15, 16)
8   position in relation to each other, characterized in that
9   said handle sections (15, 16) are permanently joined to
10   each other.

1   **Claim 2 (previously presented):**   Handle according to
2   claim 1, characterized in that the handle (11) comprises
3   two handle sections (15, 16) and that the handle (11) is
4   provided with a lever (12) and a button (13).

1   **Claim 3 (previously presented):**   Handle according to
2   claim 1 or 2, characterized in that the handle sections
3   (15, 16) are made of a plastic or metallic material and
4   permanently joined together either by welding or gluing.

1   **Claim 4 (previously presented):** Handle according to

2   claim 1, characterized in that the handle (11) is provided

3   with a lever (12) for controlling the power or the engine

4   and a safety button (13) that stops the operator from

5   increasing the power of the engine if the operator not is

6   holding his hand around the handle (11) and the safety

7   button (13) pressed.

1   **Claim 5 (currently amended):** Handle according to ~~any~~

2   ~~of the previous claims~~claim 1, characterized in that the

3   lever or levers and/or button or buttons and related

4   components are secured in the handle section (16) via a

5   supporting section (20) extending from the handle section

6   (16).

1   **Claim 6 (currently amended):** Handle according to

2   claim 5, characterized in that the supporting section (20)

3   is provided with a pocket (21) where the lever or button is

4   placed and secured by a locking pin (23) acting as the axle

5   for the lever or button, said locking pin (23) extends

6   through two openings (22) in the supporting section (20)

7   and [[an]]a hole (24) in the lever or button.

1   **Claim 7 (currently amended):** Handle according to ~~any~~

2   ~~of claim 1-4~~claim 1, characterized in that the lever or

3   levers and/or button or buttons and related components are

4   secured in the handle section (16) by a keyhole-shaped

5   opening (26) in the lever, button or component is snapped

6   on a pin (25) extending in transverse direction from the

7   handle section (16) in relation to the longitudinal axle so

8   that the lever, button or component turns around the pin

9   (25).

1   **Claim 8 (previously presented):** Handle according to

2   claim 7, characterized in that the other handle section

3   (15) is provided with a protruding circle-shaped edge (34)

4   surrounding a part or the entire pin (25) so that when the

5   handle sections are joined will the end of the pin (25) be

6   placed so that the protruding circle-shaped edge (34)

7   supports the pin (25) when exposed to high loads.

1   **Claim 9 (currently amended):** Handle according to ~~any~~

2   ~~of claim 1-4~~claim 1, characterized in that the lever or

3   levers and/or button or buttons and related components are

4   secured in the handle section (16) by a separate metallic

5   or plastic pin (31) pressed into a prepared opening in the

6   handle section (16) so that said lever or levers and/or

7   button or buttons and related components are turning around

8   the separate metallic or plastic pin (31).

1   **Claim 10 (previously presented):** Handle according to

2   claim 9, characterized in that the other handle section

3   (15) is provided with a protruding circle-shaped edge (34)

4   surrounding a part or the entire separate metallic or

5   plastic pin (25) so that when the handle sections are

6   joined will the end of the separate metallic or plastic pin

7   (25) be placed so that the protruding circle-shaped edge

8   (34) supports the separate metallic or plastic pin (25)

9   when exposed to high loads.